



GRAFFITIGUARD ICE

PRODUCT DESCRIPTION

GRAFFITIGUARD ICE is an anti-graffiti coating with highly durable effect, can be used on porous and non-porous surfaces at low temperatures.

APPLICATION

GRAFFITIGUARD ICE forms a durable protective layer so graffiti can be easily removed. **GRAFFITIGUARD ICE** is on water base and is suitable for almost any surface and due the special supplement suitable to process at low temperatures. The layer is vapor permeable and provides 7 to 10 years of protection, depending on the circumstances.

CHARACTERISTICS

- Excellent protection against penetration of graffiti and markers
- Protects the surface against atmospheric contamination and humidity
- Reduces penetration of aggressive substances
- On waterbase
- Vapor permeable
- Environment friendly
- Biologically degradable (OECD test 302 B)
- UV resistant
- Suitable for almost any surface including concrete, brickwork, wood and natural stone

TECHNICAL DATA

Colour:	White emulsion, after drying transparent layer
Smell:	Odourless
Specific weight:	0,98 kg/l
pH:	Approx. 8
Contains:	Wax emulsion

PACKAGING

10 l, 25 l and 1000 l.

OPERATING INSTRUCTIONS

Do not dilute **GRAFFITIGUARD ICE**. The minimal prescribed consumption must be used. In some situations, this may lead to a more-layers system. Stir and shake the product intensively. **GRAFFITIGUARD ICE** can be applied with a low-pressure spray or an airless-spray. Apply the second layer after the first layer has dried slightly. It must be hand dry at least. **GRAFFITIGUARD ICE** can be applied on a moist, non-wet surface. Spilled material can be easily removed with water. Internal protection painted surface can be protected by using a brush, a roller or with a low-pressure spray. Apply **GRAFFITIGUARD ICE** in minimal 2 layers.

REMOVERS

CLEANERS


PROTECTORS



APPLICATION CONDITIONS

Ambient temperature:	maximum 30°C, minimum 0°C
Surface temperature:	maximum 30°C, minimum 0°C
Relative humidity:	maximum 95% and 3°C above the dew point

DRYING

Water-resistant:	after approx. 2 hours
Dry:	after approx. 4 hours
Fully cured:	after approx. 72 hours preferable above 0°C

THEORETICAL CONSUMPTION

Consumption approx. 0,10 – 0,20 l / m². Consumption depends on the roughness of the surface.

STORAGE AND STABILITY

In original unopened package at least 12 months sustainable. Store in a dry, cool frost-free place.

SAFETY PRECAUTIONS

Wear suitable protective clothing, gloves and face protection. In case of contact with eyes, rinse with plenty of water and consult medical advice. After contact with skin, wash with water and soap. If swallowed, drink water or milk, do not induce vomiting, consult physician.

LABELING

Not classified

EDITION

August 2018

All previous editions are canceled with this release.

This product information sheet is intended as a guide for the use of the product and is drawn up on the basis of the latest development and technology. Because application and usage conditions are beyond our control, no rights can be derived from this product information sheet. MAVRO Int. rejects all liability regarding warranty and incorrect application and any damage and consequential damage. The applicator remains responsible at all times regarding application, product selection, application and result.

REMOVERS

CLEANERS



PROTECTORS