



GRAFFITIGUARD LITE

PRODUCT DESCRIPTION

GRAFFITIGUARD LITE is a long lasting protective anti-graffiti coating for highly vulnerable, porous and non-porous surfaces that require a lower pressure for the removal of graffiti. Like painted surfaces and stucco work surfaces and non-porous surfaces.

APPLICATION

GRAFFITIGUARD LITE forms a durable protective layer so graffiti can be easily removed. **GRAFFITIGUARD LITE** is on water base and suitable for almost any surface. The material forms a sacrificial layer and must be re-applied when the graffiti is removed. The layer is vapor permeable and provides 5 years of protection depending on the circumstances. Excellent for protection of sensitive surfaces like stucco and paintwork.

CHARACTERISTICS

- Excellent protection against penetration of graffiti and markers
 - Protects the surface against atmospheric contamination and humidity
 - Reduces penetration of aggressive substances
 - On waterbase
 - Vapor permeable
 - Alkali resistant
 - Environment friendly
 - Biologically degradable
 - UV-resistant
 - Suitable for almost any surface
-

TECHNICAL DATA

Colour:	White emulsion, after drying transparent layer
Smell:	Odourless
Specific weight:	1,00 kg/l
pH:	Approx. 8
Contains:	Wash emulsion
Flash point:	Does not apply

PACKAGING

10 l, 25 l and 1000 l.

OPERATING INSTRUCTIONS

GRAFFITIGUARD LITE can be applied with a low-pressure spray or airless-spray. Preferably with a sponge. Apply the second layer after the first layer has dried slightly. It must be hand dry at least. **GRAFFITIGUARD LITE** can be applied on a moist, non-wet surface. Spilled material can be easily removed with water. Painted surfaces can be protected by using a brush, roller or with a low-pressure spray. Apply **GRAFFITIGUARD LITE** in minimal 2 layers.

REMOVERS

CLEANERS


PROTECTORS



APPLICATION CONDITIONS

Ambient temperature:	maximum 30°C, minimum 10°C
Surface temperature:	maximum 30°C, minimum 10°C
Relative humidity:	maximum 95% and 3°C above the dew point

DRYING

Water-resistant:	after approx. 2 hours
Dry:	after approx. 4 hours
Fully cured:	after approx. 72 hours preferable at 10 - 35°C

THEORETICAL CONSUMPTION

Consumption approx. 5 - 10 m²/l, Consumption depends on the porosity of the surface.

STORAGE AND STABILITY

In original unopened package at least 12 months sustainable. Store in a dry, cool frost-free place.

SAFETY PRECAUTIONS

Wear suitable protective clothing, gloves and face protection. In case of contact with the eyes, immediately rinse with plenty of water and consult medical advice. After contact with the skin, wash with water and soap. If swallowed, drink water or milk, do not induce vomiting. Consult medical advice.

LABELING

Not classified

EDITION

August 2018

All previous editions are canceled with this release.

This product information sheet is intended as a guide for the use of the product and is drawn up on the basis of the latest development and technology. Because application and usage conditions are beyond our control, no rights can be derived from this product information sheet. MAVRO Int. rejects all liability regarding warranty and incorrect application and any damage and consequential damage. The applicator remains responsible at all times regarding application, product selection, application and result.

REMOVERS

CLEANERS

