



# MAVROSEAL

## PRODUCT DESCRIPTION

**MAVROSEAL** is a high-quality oligomer silane/siloxane impregnating liquid for the sustainable water repellency of mineral surfaces in facades etc.

---

## APPLICATION

**MAVROSEAL** makes the surface durable water resistant. Although somewhat dependent on the structure and the absorption capacity of the surface, **MAVROSEAL WB** penetrates deep enough to ensure effective and sustainable operation. **MAVROSEAL WB** makes the surface water repellent but remains vapor-open. The stone remains for 100% water vapor permeable; The condensation moisture formed on the inside of the wall can be discharged out of the vapor form unimpeded. The composition of **MAVROSEAL WB** can result in very slight staining of the surface. As a consequence, bold colours can be reproduced. **MAVROSEAL WB** will never give a gloss effect. Suitable for all cement-based surfaces made of sand, cement and clay. Also, on already impregnate surfaces.

---

## CHARACTERISTICS

- High penetration value
  - Hair tearing over
  - No reduction of vapor permeability
  - Applicable on two weeks old masonry
  - Due the long contact time applicable on closed surface
  - Excellent penetration on previously hydrophobic surfaces
- 

## TECHNICAL DATA

Colour:	Transparent
Smell:	Light solvent smell
Specific weight:	0,81 kg/l
pH:	Does not apply
Contains:	Naphtha, low aromatic
Flash point:	>60°C
Number of layers:	1 saturated layer (in one treatment 2 layers wet in wet)
Shape:	Liquid
Dilution:	Do not dilute

---

## PACKAGING

10 l, 25 l, 200 l en 1000 l.

---

## OPERATING INSTRUCTIONS

Apply **MAVROSEAL** evenly by the flow method with suitable spraying apparatus, or by brushing saturating the surface evenly. Get the best result when working from bottom to top.

REMOVERS

CLEANERS



PROTECTORS



## APPLICATION CONDITIONS

Ambient temperature:	maximum 30°C, minimum 5°C
Surface temperature:	maximum 30°C, minimum 5°C
Relative humidity:	maximum 95% and 3°C above the dew point

---

## DRYING

Water-resistant:	after approx. 2 hours
Dry:	after approx. 4 hours

---

## THEORETICAL CONSUMPTION

Consumption 1 – 2 m<sup>2</sup>/l. Consumption is strongly dependent of the surface.

---

## STORAGE AND STABILITY

In original unopened packaging at least 24 months sustainable. Store in a dry, cool and frost-free place.

---

## SAFETY PRECAUTIONS

Avoid contact with skin and eyes. Wear suitable protective gloves, protective clothing, safety goggles, and face protection. In case of skin contact rinse with water, then wash with soap and water. In case of contact with eyes, remove any contact lenses and rinse immediately with plenty of water and consult expert advice. In case of ingestion, drink water or milk, do not induce vomiting. For more information consult the safety data sheet.

---

## LABELING

Danger, can be fatal when swallowed.



GHS08

### EDITION

August 2018

All previous editions are canceled with this release.

This product information sheet is intended as a guide for the use of the product and is drawn up on the basis of the latest development and technology. Because application and usage conditions are beyond our control, no rights can be derived from this product information sheet. MAVRO Int. rejects all liability regarding warranty and incorrect application and any damage and consequential damage. The applicator remains responsible at all times regarding application, product selection, application and result.

REMOVERS

CLEANERS

**PROTECTORS**

Article no.: 54060

MAVRO International T:+31 418 680 680 info@mavro-int.com www.mavro-int.com

2018-08-23 page 2 of 2