



MAVROSEAL WB EXTRA STRONG

PRODUCT DESCRIPTION

MAVROSEAL WB EXTRA STRONG is a waterborne silane and siloxane water repellent impregnation agent for all types of cement-based surfaces. Very suitable for already impregnated surfaces.

APPLICATION

MAVROSEAL WB EXTRA STRONG makes the surface durable water resistant. Although slightly dependent on the structure and the absorption capacity of the surface, **MAVROSEAL EXTRA STRONG** penetrates sufficiently deeply to ensure effective and lasting operation. **MAVROSEAL EXTRA STRONG** makes the surface water repellent but not vapor-tight. The stone remains for 100% water vapor permeable; The condensation moisture formed on the inside of the wall can be discharged out of the vapor form unimpeded. The composition of **MAVROSEAL EXTRA STRONG** can result in a slight colour accentuation of the surface. As a consequence, bold colours can be reproduced. **MAVROSEAL EXTRA STRONG** will never give a gloss effect. Suitable for all cement-based surfaces made of sand, cement and clay. Also, on already impregnated surfaces.

CHARACTERISTICS

- Very high penetration value
- Alkali-resistant
- Water repellency
- 100% vapor permeable
- Inside and outside applicable
- Also suitable for concrete
- Environment and processing friendly
- UV-resistant
- Applicable to fresh masonry

TECHNICAL DATA

Colour:	White emulsion, after drying transparent layer
Smell:	Light alcoholic smell
Specific weight:	0,96 kg/l
pH:	Approx. 6
Contains:	Siloxane
Flash point:	Does not apply
Number of layers:	1 saturated layer (2 treatments wet in wet)
Shape:	Liquid
Dilution:	Do not dilute

PACKAGING

10 l, 25 l, 200 l en 1000 l.

OPERATING INSTRUCTIONS

Apply **MAVROSEAL WB EXTRA STRONG** uniformly and saturate through the flow method with suitable spray or application with roller or brush. Get the best result when working from bottom to top.

REMOVERS

CLEANERS


PROTECTORS



APPLICATION CONDITIONS

Ambient temperature: maximum 30°C, minimum 10°C
Surface temperature: maximum 30°C, minimum 10°C
Relative humidity: maximum 95% and 3°C above the dew point

DRYING

Water-resistant: after approx. 2 hours
Dry: after approx. 4 hours

THEORETICAL CONSUMPTION

Consumption ca. 1 – 2 m²/litre. Consumption depends on the surface, roughness and porosity.

STORAGE AND STABILITY

In original unopened packaging at least 24 months sustainable. Store in a cool, dry, well-ventilated frost-free place.

SAFETY PRECAUTIONS

Wear protective gloves, protective clothing and eye / face protection. For more information consult the safety data sheet.

LABELING

Not classified

EDITION

August 2018

All previous editions are canceled with this release.

This product information sheet is intended as a guide for the use of the product and is drawn up on the basis of the latest development and technology. Because application and usage conditions are beyond our control, no rights can be derived from this product information sheet. MAVRO Int. rejects all liability regarding warranty and incorrect application and any damage and consequential damage. The applicator remains responsible at all times regarding application, product selection, application and result.

REMOVERS

CLEANERS


PROTECTORS