



MAVROSEAL WB STRONG

PRODUCT DESCRIPTION

MAVROSEAL WB STRONG is a waterborne, water repellency impregnating agent for mineral surfaces based on silanes and siloxanes. **MAVROSEAL WB STRONG** has a sustainable effect and a strong pearling effect.

APPLICATION

MAVROSEAL WB STRONG makes the surface durable water resistant. Although somewhat depends on the structure and the absorption capacity of the surface, **MAVROSEAL WB STRONG** penetrates sufficiently deeply to ensure effective and lasting operation. **MAVROSEAL WB STRONG** makes the surface water repellent but not vapor-tight. The stone remains 100% water vapor permeable; The condensation moisture formed on the inside of the wall can be discharged out of the vapor form unimpeded. The composition of **MAVROSEAL WB STRONG** can result in a slight colour accentuation of the surface. As a consequence, bold colours can be reproduced.

CHARACTERISTICS

- High penetration value
- Alkali-resistant
- 100% vapor permeable
- Inside and outside applicable.
- Also suitable for concrete
- Environment and processing friendly
- UV resistant
- Applicable to fresh masonry

TECHNICAL DATA

| | |
|-------------------|--|
| Colour: | White emulsion, after drying transparent layer |
| Smell: | Odourless |
| Specific weight: | 1,0 kg/l |
| pH: | Approx. 7 |
| Flash point: | Not applicable |
| Number of layers: | 1 saturated layer (in one treatment 2 layers wet in wet) |
| Shape: | Liquid |
| Dilution: | Do not dilute |

PACKAGING

10 l, 25 l, 200 l en 1000 l.

OPERATING INSTRUCTIONS

Apply **MAVROSEAL WB STRONG** uniformly and saturating through the flow method with suitable spray or application with roller or brush. Get the best result when working from bottom to top.

REMOVERS

CLEANERS



PROTECTORS



APPLICATION CONDITIONS

Ambient temperature: maximum 30°C, minimum 5°C
Surface temperature: maximum 30°C, minimum 5°C
Relative humidity: maximum 95% and 3°C above the dew point during application and drying

DRYING

Water-resistant: after approx. 2 hours
Dry: after approx. 4 hours

THEORETICAL CONSUMPTION

Consumption 1 – 2 m²/l. Consumption depends on the porosity and suction of the surface.

STORAGE AND STABILITY

In original unopened packaging at least 12 months sustainable. Store in a dry, cool and frost-free place.

SAFETY PRECAUTIONS

Wear protective gloves, protective clothing and eye / face protection. For more information consult the safety data sheet.

LABELING

Not classified

EDITION

August 2018

All previous editions are canceled with this release.

This product information sheet is intended as a guide for the use of the product and is drawn up on the basis of the latest development and technology. Because application and usage conditions are beyond our control, no rights can be derived from this product information sheet. MAVRO Int. rejects all liability regarding warranty and incorrect application and any damage and consequential damage. The applicator remains responsible at all times regarding application, product selection, application and result.

REMOVERS

CLEANERS


PROTECTORS