



# MAVROSEAL

## PRODUCT DESCRIPTION

**MAVROSEAL** is a waterborne impregnation agent based on van silane/siloxane for mineral substrates. **MAVROSEAL WB** has a durable working and strong beading effect.

---

## APPLICATION

**MAVROSEAL GEL** makes the surface durable water-resistant. Although some dependent on the structure and absorption capacity of the subsoil, **MAVROSEAL WB** penetrates deep enough to ensure effective and sustainable operation. **MAVROSEAL WB** makes the surface water-repellent but not vapor-tight. The stone remains permeable for 100% water vapor; the condensation moisture that may form on the inside of the wall can be discharged unobstructed in the vapor form. The composition of **MAVROSEAL WB** can result in a slight colour accentuation of the substrate. This makes it possible to speak pale colours again.

---

## CHARACTERISTICS

- High penetration value
  - Alkali resistant
  - 100% vapor permeable
  - Can be used inside and outside
  - Suitable for concrete stone
  - Environment and processing friendly
  - UV resistant
  - Applicable on new jointing
- 

## TECHNICAL DATA

Colour:	White emulsion, after drying transparent layer
Smell:	Odourless
Specific weight:	1,00 kg/l
pH:	Approx. 7
Flash point:	Does not apply
Number of layers:	Saturate 1 layer (in one treatment, two layers wet in wet)
Shape:	Liquid
Dilution:	Ready for use, do not dilute

---

## PACKAGING

10 l, 25 l, 200 l, en 1000 l IBC.

---

## OPERATING INSTRUCTIONS

Apply **MAVROSEAL** evenly and saturating by means of the flux method with suitable spray or application with roller or brush. The best result is obtained when working from bottom to top.

REMOVERS

CLEANERS

PROTECTORS



## APPLICATION CONDITIONS

Ambient temperature: maximum 30°C, minimum 10°C  
Surface temperature: maximum 30°C, minimum 10°C  
Relative humidity: maximum 95% and 3°C above the dew point while applying and drying

---

## DRYING

Water-resistant: after approx. 2 hours  
Dry: after approx. 4 hours

---

## THEORETICAL CONSUMPTION

Consumption: 1 – 2 m<sup>2</sup>/l. Consumption depends on the porosity and the suction of the surface.

---

## STORAGE AND STABILITY

In original unopened packaging at least 12 months sustainable. Store in a dry frost-free area.

---

## SAFETY PRECAUTIONS

Wear resistant gloves, protective clothing and eye or face protection. For more information consult the safety sheet.

---

## LABELING

Not classified

### EDITION

August 2018

All previous editions are canceled with this release.

This product information sheet is intended as a guide for the use of the product and is drawn up on the basis of the latest development and technology. Because application and usage conditions are beyond our control, no rights can be derived from this product information sheet. MAVRO Int. rejects all liability regarding warranty and incorrect application and any damage and consequential damage. The applicator remains responsible at all times regarding application, product selection, application and result.

REMOVERS

CLEANERS

  
**PROTECTORS**