



MAVROX EP GROUT 2C

PRODUCT DESCRIPTION

MAVROX EP GROUT 2C is a solvent-free 2-component mortar based on special Epoxy resins.

APPLICATION

MAVROX EP GROUT 2C can be used for the sub-casting of structures, the filling of holes and the bonding of tie-rods and high tensile bolts, where high strength is required.

CHARACTERISTICS

- Solvent free
 - Odourless
 - Not flammable
 - Good chemical resistance
 - Perceptible pot-life
 - Very durable
 - Shrink-free
 - Good adhesion on concrete
-

TECHNICAL DATA

Colour:	Beige
Smell:	Odourless
Specific weight:	Approx. 1,75 kg/l
pH:	Does not apply
Contains:	Epoxy resins
Number of layers:	Does not apply
Solid content:	100%
Shape:	Viscous liquid
Dilution:	Do not dilute
Viscosity:	800 - 1500 mPas
Potlife:	15 minutes at 20°C

PACKAGING

Units of 5 kg.

OPERATING INSTRUCTIONS

Components must be thoroughly mixed in their entirety. Pour component B (hardener) completely into the packaging of component A (resin) mechanically mixing at a low speed, such that little air strikes, for approx. 3 minutes, until a homogeneous mass in one colour is formed. After mixing, pour the mass into a clean mixing can and mix again for 1 minute. **MAVROX** EP GROUT 2C can be applied by casting. The formwork against adhesion provided with plastic film or grease.



SPECIALTIES

Article no.: 57922



APPLICATION CONDITIONS

Ambient temperature: maximum 30°C, minimum 10°C
Surface temperature: maximum 30°C, minimum 10°C
Relative humidity: maximum 85% and 3°C above the dew point

DRYING

Dust dry: 2 - 3 hours
Dry: after approx. 8 - 10 hours
Paintable: after 24 hours
Fully cured: after 2 days, fully chemically curable

THEORETICAL CONSUMPTION

Does not apply.

STORAGE AND STABILITY

In original unopened packaging **MAVROX** EP GROUT 2C is at least 6 months sustainable in a dry and cool place. Store between 0°C and + 30°C.

SAFETY PRECAUTIONS

Avoid contact with skin and eyes. Wear suitable protective gloves, protective clothing, safety glasses and face protection. Ensure good ventilation when used indoors. Consult the safety data sheet.

LABELING

Danger. Harmful when inhaled or swallowed.



GHS07

EDITION

August 2018

All previous editions are canceled with this release.

This product information sheet is intended as a guide for the use of the product and is drawn up on the basis of the latest development and technology. Because application and usage conditions are beyond our control, no rights can be derived from this product information sheet. MAVRO Int. rejects all liability regarding warranty and incorrect application and any damage and consequential damage. The applicator remains responsible at all times regarding application, product selection, application and result.



SPECIALTIES

Article no.: 57922