



MAVROX EP SCREED 3C

PRODUCT DESCRIPTION

MAVROX EP SCREED 3C is a solvent-free 3 components coloured, trawlable mortar based on epoxy resins with high wear resistance and chemical resistance.

APPLICATION

MAVROX EP SCREED 3C is an all-round mortar usable in a lot of different industries where the floor is exposed to heavy loads. Also usable on galleries, balconies, parking garages and warehouses. Also, suitable to create a slope or to restore the existing gradient.

CHARACTERISTICS

- Sustainable
- Heavily taxable
- Decorative
- Liquid-tight
- Chemically resistant
- Easy to clean
- Different colors available
- Resistant to de-icing salts and thermo shock

TECHNICAL DATA

Colour:	Available in 5 standard colours
Smell:	Product typical
Specific weight:	2,1 kg/l
pH:	Not applicable
Contains:	Epoxy resin average mol weight. < 700 Dalton
Number of layers:	1 - 2
Shape:	Viscous liquid
Dilution:	Do not dilute
Viscosity:	800 - 1500 mPas
Potlife:	Approx. 35 minutes at 20°C
VOC content:	Product is solvent free

PACKAGING

30 kg and 60 kg.

OPERATING INSTRUCTIONS

Add **MAVROX EP SCREED 3C** component B to component A. Mix well until homogenous. Transfer components A and B to a mixing tub and add component C. Thoroughly mix the whole, preferably with a mechanical/electric mixer.

REMOVERS

CLEANERS





APPLICATION CONDITIONS

Ambient temperature:	maximum 30°C, minimum 10°C
Surface temperature:	maximum 30°C, minimum 10°C
Relative humidity:	maximum 85% and 3°C above the dew point

DRYING

Dust-dry:	1 - 1,5 hours
Fully cured:	after approx. 6 - 8 hours
Repaintable:	after 24 hours
Fully hardend:	after 4 - 7 days

THEORETICAL CONSUMPTION

Consumption depends on the applied layer: 1 m² at a layer thickness of 1 gives a consumption of 21 kg.

STORAGE AND STABILITY

In original unopened packaging is **MAVROX** EP SCREED 3C at least 12 months sustainable when stored in a dry and cool place.
Store between + 0°C and + 30°C

SAFETY PRECAUTIONS

During processing, avoid skin and eye contact. Wear suitable protective clothing such as gloves and safety glasses. Ensure good ventilation when used indoors. Consult the safety data sheet.

LABELING

Danger. Harmful when ingested and inhaled.



GHS07

EDITION

August 2018

All previous editions are canceled with this release.

This product information sheet is intended as a guide for the use of the product and is drawn up on the basis of the latest development and technology. Because application and usage conditions are beyond our control, no rights can be derived from this product information sheet. MAVRO Int. rejects all liability regarding warranty and incorrect application and any damage and consequential damage. The applicator remains responsible at all times regarding application, product selection, application and result.

REMOVERS

CLEANERS

PROTECTORS

Article no.: 57914

MAVRO International T:+31 418 680 680 info@mavro-int.com www.mavro-int.com

2018-08-23 page 2 of 2