



# NITOCRYL PRIMER

## PRODUCT DESCRIPTION

**NITOCRYL PRIMER** is a waterborne primer for acrylic systems like the strippable NITOCRYL and can be used for application on various surfaces.

## APPLICATION

**NITOCRYL PRIMER** is a sealant/primer for finishing with waterborne systems like **NITOCRYL** and is applicable on high pressure laminated sheet, powder coated and anodised aluminium, non-ferrous metals and cement-bonded sheet materials and other mineral substrates. Apply a minimum of two layers for application as primer and finish. Very suitable as a primer on various surfaces with the strippable finish **NITOCRYL**. **NITOCRYL PRIMER** is not alkali-strippable and is, if desired, to be removed with a mild paint stripper, or a solvent-based graffiti remover.

## CHARACTERISTICS

- Provides excellent adhesion to coatings like **NITOCRYL**
- Excellent adhesion on porous and non-porous surfaces
- Very well applicable to Plastisol coating
- Simple application
- Transparent silk
- Less environmentally harmful

## TECHNICAL DATA

Colour:	White/transparent liquid
Smell:	Neutral mild
Specific weight:	1,03 kg/l
pH:	6 - 8
Flash point:	Does not apply
Boiling point:	Approx. 100°C
Shape:	Thin liquid
Viscosity:	150 - 300 mPas
VOC content:	Classification cat. e/wg-max. 130 g/l. This product contains 45 g/later VOC

## PACKAGING

1 l and 5 l.

## OPERATING INSTRUCTIONS

Apply **NITOCRYL PRIMER** undiluted on a clean, dry surface with a roller, wiper or microfibre cloth. Spray with HVLP up to a maximum of 10% dilution with water.

REMOVERS

CLEANERS

**PROTECTORS**



## APPLICATION CONDITIONS

Ambient temperature: maximum 30°C, minimum 10°C  
Surface temperature: maximum 30°C, minimum 10°C  
Relative humidity: maximum 85% and 3°C above the dew point

---

## DRYING

Dust-dry: 1 - 1,5 hours  
Dry: after approx. 6 - 8 hours  
Waterproof: after 24 hours

---

## THEORETICAL CONSUMPTION

Consumption 10 – 14 m<sup>2</sup>/liter. Consumption depends on the suction of the surface and the application method.

---

## STORAGE AND STABILITY

In original unopened packaging for at least 12 months sustainable. Store in a dry, cool, frost-free place.

---

## SAFETY PRECAUTIONS

Wear protective clothing, suitable gloves and eye protection.

---

## LABELING

Not classified

### EDITION

August 2018

All previous editions are canceled with this release.

This product information sheet is intended as a guide for the use of the product and is drawn up on the basis of the latest development and technology. Because application and usage conditions are beyond our control, no rights can be derived from this product information sheet. MAVRO Int. rejects all liability regarding warranty and incorrect application and any damage and consequential damage. The applicator remains responsible at all times regarding application, product selection, application and result.

REMOVERS

CLEANERS

  
**PROTECTORS**

Article no.: 57711

**MAVRO** International T:+31 418 680 680 info@mavro-int.com www.mavro-int.com

2018-08-23 page 2 of 2