



NITOWAX

PRODUCT DESCRIPTION

NITOWAX is a cleaning and maintenance product for weathered surfaces such as slightly weathered plastics, powdered and chalking coatings and weathered car paints.

APPLICATION

NITOWAX is very suitable for cleaning and temporarily preserving smooth and closed surfaces like plastic frames and fittings, coated sheet material and hpl plate. After rinsing or wiping, the product leaves a light, protective wax layer behind.

CHARACTERISTICS

- Gives a hydrophobic surface
- Suitable for many surfaces
- Easy application
- Durability up to 1,5 years

TECHNICAL DATA

Colour:	White/beige emulsion, after drying and processing transparent
Smell:	Product typical
Specific weight:	1,02 kg/l
pH:	Approx. 7
Contains:	Hydrocarbons
Flash point:	>65°C
Boiling point:	>100°C
Shape:	Light viscous liquid
Dilution:	Do not dilute
Viscosity:	50 - 100 mPas
VOC content:	Not classified

PACKAGING

1 l, 5 l and 10 l.

OPERATING INSTRUCTIONS

Before applying **NITOWAX** clean and rinse the surface using **UNICLEAN LOW FOAMING**. Then degrease and dry the surface with **ISOPROPANOL**. Apply the **NITOWAX** to a lint-free microfiber cloth or humid power sponge and spread evenly on the surface. Allow to dry for a couple of minutes. If necessary, lightly wipe with a soft microfiber cloth. For highly absorbent and powdered substrates, a second layer can be applied "wet in wet" with an intermediate drying time up to 30 minutes.

APPLICATION CONDITIONS

Ambient temperature:	maximum 30°C, minimum 10°C
Surface temperature:	maximum 30°C, minimum 10°C
Relative humidity:	maximum 85% and 3°C above the dew point

REMOVERS

CLEANERS



PROTECTORS



DRYING

Dust-dry:	0,5 - 1 hour
Dry:	after approx. 2 - 4 hours
Waterproof:	after 6 - 8 hours

THEORETICAL CONSUMPTION

Consumption 12 – 25 m²/l. Consumption depends on the roughness, degree of weathering of the surface and application method.

STORAGE AND STABILITY

In original unopened packaging for at least 12 months sustainable. Store in a dry, cool, frost-free place.

SAFETY PRECAUTIONS

Wear suitable resistant gloves, protective clothing and safety glasses. Avoid contact with eyes and skin. For more information consult the safety sheet.

LABELING

Danger. May be fatal if swallowed.



GHS08

EDITION

August 2018

All previous editions are canceled with this release.

This product information sheet is intended as a guide for the use of the product and is drawn up on the basis of the latest development and technology. Because application and usage conditions are beyond our control, no rights can be derived from this product information sheet. MAVRO Int. rejects all liability regarding warranty and incorrect application and any damage and consequential damage. The applicator remains responsible at all times regarding application, product selection, application and result.

REMOVERS

CLEANERS


PROTECTORS

Article no.: 99900

MAVRO International T:+31 418 680 680 info@mavro-int.com www.mavro-int.com

2018-08-23 page 2 of 2