



FLOORGUARD FLUOR

PRODUCT DESCRIPTION

FLOORGUARD FLUOR is a waterborne impregnating liquid based on fluoropolymers for light porous mineral surfaces.

APPLICATION

FLOORGUARD FLUOR gives the surface a durable water, grease and oil repellent finish. Depending on the structure and the absorption capacity of the surface, **FLOORGUARD FLUOR** penetrates into the surface and provides an effective and lasting effect. **FLOORGUARD FLUOR** makes the surface water repellent and provides an easy to clean surface and allows the surface to be vapor-open.

CHARACTERISTICS

- Provides a hydrophobic and oily surface
 - Suitable for a variety of mineral surfaces
 - Simple application
 - Durable and wear resistant
-

TECHNICAL DATA

Colour:	White emulsion, after drying transparent
Smell:	Product typical
Specific weight:	1,02 kg/l
pH:	Approx. 6
Contains:	Fluor acrylate polymer
Flash point:	Not applicable
Boiling point:	>100°C
Number of layers:	Apply in two layers wet in wet with a drying time - in between the two layers- of maximal 30 minutes.
Shape:	Liquid

PACKAGING

10 l

OPERATING INSTRUCTIONS

Remove all contaminants like old layers of wax, grease, dirt etc. by cleaning with **UNICLEAN LOW FOAMING** and a floor scrubbing device. Flush thoroughly using a high-pressure water-jet. Allow to completely dry. In most cases one layer is sufficient, if necessary apply a second layer wet in wet with a drying time - in between the two layers- of maximal 30 minutes. Use **FLOORGUARD EXTERIOR** undiluted and apply with wiper or shorthaired roller. Remove excess with a lint-free cloth.

APPLICATION CONDITIONS

Ambient temperature:	maximum 30°C, minimum 10°C
Surface temperature:	maximum 30°C, minimum 10°C
Relative humidity:	maximum 85% and 3°C above the dew point

REMOVERS

CLEANERS

PROTECTORS



DRYING

Dust-dry:	10 - 20 minutes
Dry:	after approx. 1 - 1,5 hours
Paintable:	n.a. second layer wet in wet
Fully cured:	after 6 - 8 hours

THEORETICAL CONSUMPTION

Use 5 – 10 m²/l. Usage depends on the roughness and porosity of the surface.

STORAGE AND STABILITY

In original unopened packaging for at least 12 months sustainable. Store in a dry, cool, frost-free place.

SAFETY PRECAUTIONS

Wear protective clothing and suitable gloves.

LABELING

Not classified

EDITION

December 2018

All previous editions are canceled with this release.

This product information sheet is intended as a guide for the use of the product and is drawn up on the basis of the latest development and technology. Because application and usage conditions are beyond our control, no rights can be derived from this product information sheet. MAVRO Int. rejects all liability regarding warranty and incorrect application and any damage and consequential damage. The applicator remains responsible at all times regarding application, product selection, application and result.

REMOVERS

CLEANERS


PROTECTORS

Article no.: 57644

MAVRO International T:+31 418 680 680 info@mavro-int.com www.mavro-int.com

2018-12-19 page 2 of 2