



FLOORGUARD SB

PRODUCT DESCRIPTION

FLOORGUARD SB is a high-quality 1 component waterborne sealer for cement-bound floors, anhydrite and (poured) asphalt.

APPLICATION

FLOORGUARD SB is a highly efficient sealer for transparent sealing of floors, both inside and outside. For improving the top layer of the floor and binding of all dust. Apply directly to monolithic or unfinished floors that have been cleaned and are cleared of curing-compounds and other adhesion-inhibiting substances. Typical applications are offices, garages, basements, warehouse floors, ventilation ducts, poured asphalt, production areas and food storage.

CHARACTERISTICS

- Water-borne and vapor-permeable
 - Easy to apply
 - Durable, low maintenance costs
 - UV resistant
 - Dust-free
 - Fast curing
-

TECHNICAL DATA

Colour:	White emulsion, after drying transparent layer
Smell:	Characteristic odour
Specific weight:	1,03 kg/l
pH:	Approx. 6
Flash point:	Not applicable

PACKAGING

10 l and 25 l.

OPERATING INSTRUCTIONS

Apply **FLOORGUARD SB** evenly with a brush, roller or strip washer. Allow the product to dry for about 15 - 30 minutes. Material that has not been absorbed after this period must be removed. Not doing this will result in the formation of a brittle, weak, shiny surface. Construction: cement-bound floors 1 to 3 layers of **FLOORGUARD SB**. Anhydrite 2 to 3 layers **FLOORGUARD SB** Casting 2 to 3 layers **FLOORGUARD SB**. Surface conditions: Floor should be oil, grease and dust free. Possible repairs with **PATCHROC GP** or 630 and allow to hardening.

APPLICATION CONDITIONS

Ambient temperature:	maximum 30°C, minimum 10°C
Surface temperature:	maximum 30°C, minimum 10°C
Relative humidity:	maximum 85% and 3°C above the dew point

REMOVERS

CLEANERS


PROTECTORS



DRYING

Water-resistant:	after 2 hours
Dry:	after 4 hours
Fully hardened:	after 72 hours

THEORETICAL CONSUMPTION

Consumption approx. 1 - 10 m²/l. Consumption depends on the nature and porosity of the surface.

STORAGE AND STABILITY

In original unopened package at least 12 months sustainable. Store in a dry, cool place with temperatures between 5°C - 30°C.

SAFETY PRECAUTIONS

Wear protective gloves and wear eye/face protection. For more information consult the safety data sheet.

LABELING

Not classified

EDITION

December 2018

All previous editions are canceled with this release.

This product information sheet is intended as a guide for the use of the product and is drawn up on the basis of the latest development and technology. Because application and usage conditions are beyond our control, no rights can be derived from this product information sheet. MAVRO Int. rejects all liability regarding warranty and incorrect application and any damage and consequential damage. The applicator remains responsible at all times regarding application, product selection, application and result.

REMOVERS

CLEANERS


PROTECTORS

Article no.: 57831

MAVRO International T:+31 418 680 680 info@mavro-int.com www.mavro-int.com

2018-12-19 page 2 of 2