



# STRIP-OFF HD

## PRODUCT DESCRIPTION

**STRIP-OFF HD** is an effective paint stripper gel, based on a combination of formic acid and benzyl alcohol.

---

## APPLICATION

**STRIP-OFF HD** removes all 1 and 2 component varnishes and pigmented coatings, like epoxy and polyurethane and both water-based and synthetic paints and coatings. Removes glue residues like carpet glue, glass fabric wall covering including wall paint, graffiti on bare concrete and brick and removes wax layers. Can damage lime containing natural stone.

---

## CHARACTERISTICS

- For inside and outside use
  - Biologically degradable (OECD test 302B)
  - Methylene chloride free
  - N-Methyl-2-Pyrrolidone (NMP) free
  - Long open time (up to 48 hours)
  - Wooden can be bleached
  - Thixotropic composition, perfectly vertical to process (does not sag or drip)
- 

## TECHNICAL DATA

Colour:	Green dyed
Smell:	Formic acid and pine
Specific weight:	1,1 kg/l
pH:	Approx. 2
Contains:	Formic acid and benzyl alcohol
Flash point:	>70°C

---

## PACKAGING

5 l, 10 l and 25 l.

---

## OPERATING INSTRUCTIONS

Apply **STRIP-OFF** in a thick and even layer on the surface using a brush or roller and leave for 30 minutes - 36 hours.

At lower temperatures or thicker paint layers leave for longer times and cover the **STRIP-OFF HD** with a plastic sheet.

Remove the paint residue with a spatula and filling knife and clean the surface with water under high pressure, 50 – 300 bar depending on the surface and paint residues. After cleaning rinse with clean tap-water.

If necessary repeat the procedure.

---

## APPLICATION CONDITIONS

**STRIP-OFF** can be used in all dry weather conditions. Temperatures below 10°C can slow the effectiveness of the product.

---

## THEORETICAL CONSUMPTION

Consumption is approx. 0,3 - 1 l/m<sup>2</sup>. Consumption is strongly dependent on the thickness and nature of the layers to be removed.

---



**REMOVERS**

**CLEANERS**

**PROTECTORS**

Article no.: 57647



### STORAGE AND STABILITY

In original unopened packaging at least 24 months sustainable. Store in a cool, well ventilated and frost-free place.

---

### SAFETY PRECAUTIONS

Wear suitable protective gloves, protective clothes and safety glasses or face mask. Avoid eye and skin contact. For more information consult the safety data sheet. Use only in well-ventilated areas.

---

### LABELING

DANGER. Corrosive. May cause severe skin burn and damage to the eyes.



GHS05

#### EDITION

December 2018

All previous editions are canceled with this release.

This product information sheet is intended as a guide for the use of the product and is drawn up on the basis of the latest development and technology. Because application and usage conditions are beyond our control, no rights can be derived from this product information sheet. MAVRO Int. rejects all liability regarding warranty and incorrect application and any damage and consequential damage. The applicator remains responsible at all times regarding application, product selection, application and result.



**REMOVERS**

**CLEANERS**

**PROTECTORS**

Article no.: 57647